







Alzahy Gloss Alkyd

Description and features

Application

concrete surface:

1 - The surfaces should be flat clean and completely dry.

to the coloring system of Almadina misurata paints

- 2 Apply one coat of (alzawaq Insulator Almadina Misurata).
- 3 Apply two or three coats of (Almadina misurata putty) With lengthwise and widthwise sand it and clean the dust.

High Quality Exterior and Interior Gloss Bright white Alkyd Paint, High coverage, Anti - yellowing, used for cement, concrete. wood and iron surfaces, Available in white and 2224 other colors according

- 4 Apply one coat of (Almadina misurata Matt Alkyd paint)
- 5 Apply one or two coats of Alzahy Gloss Alkyd After dilution 10-15 % by mineral turpentine water one day should be allowed between the coats.

Iron Surfaces:

- 1 The surfaces should be flat clean and completely dry.
- 2 Apply one coat for The new surfaces by (Almadina misurata Anti rust primer)
- 3 Apply one or two coats of Alzahy Gloss Alkyd After dilution 10-15 % by mineral turpentine water one day should be allowed between the coats.

Physical constant

White and colors Color Specific gravity 1.2 ± 0.05 Kg/l Viscosity 110:115 Krebs Spreading rate 10:12 m2/1kg

Dry to touch 3 hours and completely dry after 24 hours.

Thinner Packaging 3 kg

Tools

Brush



Roller



Spray gun

Storage

Health & Safety

Product should be stored in the original package for 24 months from the production date, store it under normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales:

00218912125435

amppaints

amppaints1

www.amp.ly



