



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Roads & Pavements Paints

Description and features

acrylic and C.R paint, high-quality, resistance to weather conditions ,chemical and petroleum materials, anti-friction, , made from the finest raw material in the world, used for roads planning and parking lots , sports stadiums and for painting sidewalks

Application

- 1 - Surface must be soft ,clean, free of dirt, oil and grease to be painted.
- 2 - Apply coat or more of "Roads & Pavements Paints "using brush, Rolla and spray gun.
- 3 - for the second coat , leave 45 minutes after the first coat.

Physical constant

Color	Black, white, yellow and other colors
Solids ratio	Not less than 60% by weight
Specific gravity	1.42 ± 0.05 kg / lt
Coverage	4 : 5m ² / kg
Minimum thickness of the layer	150: 200 μ
Dry to touch	10:15 minutes
Completely drying time	60 minutes
Packing	16 kg

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints