



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Lepits

Description and features

Acrylic textured paint, interior and exterior, high quality, easy to apply, water repellent, resistant to all weather conditions, resistant to erosion and spalling, helps to hide plaster defects, it gives an old appearance of the exterior walls, And ensures a maximum protection for the walls, made from the finest materials in the world.

Application

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Apply the new surfaces with "AlZwaq Insulator".
- 3 - Apply coat of Lepits Al Madina Misurata by using the special trowel

Physical constant

Color	Available in 23 colors by catalog
Gloss	Matt
Viscosity	70 : 120 g/cm ³
Specific gravity	1.80 ± 0.05 Kg/l
Spreading rate	1 : 2 m ² /kilo
Completely Dry	24 hours
Thinner	Water By desire
PH	8 : 9
Packaging	15 kg



Trowels

Tools

Storage

Product should be stored in the original package for 12 months from the production date, store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

Twitter icon amppaints

Instagram icon amppaints

www.amp.ly