



# دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



## Kelmingaro

### Description and features

Emulsion paint , economic, interior, with high viscosity, excellent hiding power and high smoothness, made of high quality acrylic material, available in white and used on interior surfaces “cement , concrete and gypsum”.

### Application

- 1- All surfaces should be flat, clean and completely dry to be painted
- 2- Apply the new surfaces with Primer Interior ( Al zawaq insulator )
- 3- Apply two or three coats with wall Putty “ Almadina Misurata “ lengthwise, use sanding paper and then clean the dust.

### Physical constant

Color	White
Specific gravity	1.65 : 1.7 kg / l
Viscosity	125 : 135 Krebs
Spreading rate	3 : 4 m <sup>2</sup> / kilo
PH	8.5 ± 0.5
Dry to touch	1/2 hours and completely dry after 6 hours.
Flash Point	Non flammable
Thinner	Water
Thinning	water by 15% first coat ,10% second coat of total weight, depending on the thickness of the paint and the state of the surface to be coated.
Weight	15 Kg - 18 kg

### Tools



Brush



Roller



Spray gun

### Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

### Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

[www.amp.ly](http://www.amp.ly)

amppaints

amppaints