

Description

and features

Application

دهانات المدينه مصرانه

Almadina Misurata Paints



Gloss Alkyd Paint (Colors)

High Quality Exterior and Interior Gloss Alkyd Paint, High coverage, anti - Yellowing, used for cement, concrete, wood and iron surfaces.

Concrete surface :

- 1 The surfaces should be flat, clean and completely dry.
- 2 Apply one coat of (Al zawaq insulator Almadina misurata)

3 - Apply two or three coats of (Almadina Misurata putty) with lengthwise and widthwise, sand it and clean the dust.

4 - Apply one coat of (Almadina Misurata Matt Alkyd Paint).

5 - Apply one or two coats of (Almadina Misurata Gloss Alkyd) After dilution about 10 - 15 % by mineral turpentine water one day should be allowed between the coats.

Iron Surfaces :

1 - The surfaces should be flat, clean and completely dry.

2 - Apply one coat for The new surfaces by (Almadina Misurata Anti - Rust Primer) .

3 - Apply one or two coats of (Almadina Misurata Gloss Alkyd) After dilution about 10 - 15 % by mineral turpentine water one day should be allowed between the coats.



Libya – Misurata – Industrial Zone – Alaswak Marketing : C 00218918000047 marketing@almadinamisurata.com amppaints1 amppaints Sales : **C** 00218912125435 amppaints amppaints

www.amp.ly