



Decorative Putty



Description and features

Decorative Putty, high-quality, characterized by high-power glue, excellent water resistance, too high viscosity gives greater thickness as possible without any cracks or dripping, gives greater thickness of template in brick pharaonic industry, made from the finest material in the world , used for the final interior layers on concrete and cement and gypsum.

Application

- 1 All surfaces should be flat, clean and completely dry to be painted.
- 2 Apply new coat with alzawaq insulator Almadina misurata .
- 3 Apply two or three coats with "Al Madina Misurata Putty "," lengthwise and sideways", use sanding paper and then clean the dust.
- 4 Apply preparation coat of Al Madina Misurata "Latex Plus Matt".
- 5 Spread coat of decorative putty by using trowel of appropriate thickness then drawing it according to the desired form.
- 6 Leave it to dry for 12 hours s and then start sanding it by soft sandpaper.
- 7 Apply coat or two of Almadina Misurata"Silk" or "Classic Semi-Gloss".
- 8 Start aging by "Glaze" or touch it by "Decor" gold or silver according to the desire to give attractive form.

Physical constant

White Color

Specific gravity $1.71 \pm 0.03 \text{ Kg/l}$ 220:225 gm./cm3 Viscosity

spreading rate According to the thickness required

PH

Dilution Ready for use without dilution

20: 30 minutes Dry to touch 12 hours Completely dry Hardness 48 hours

Packing 5 kg, 10 kg, 25 kg

Tools

Trowels

Storage

Health & Safety

Product should be stored in the original package for 12 months from the production date, store it under normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales: 00218912125435







amppaints