

دهانات المدينه مصرانه

Almadina Misurata Paints



Epoxy Resin 210

Epoxy resin for mold casting for antiques Tables and accessories It gives high transparency like crystal

and features

Description

Color
Composite weight
Composite weight
Solids content
Mixixng ratio
drying time

completely dry

0 1

crystal clear 750 A gm 250 B gm 100 % 3 A : 1 B 12 Hours 24 Hours

Tools

Physical

constant

Storage

Health & Safety The product is stored in his original package for 24 months from the production date. Under appropriate natural conditions The product should not be exposed to direct sunlight

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.

3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .

4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak Marketing : C 00218918000047 marketing@almadinamisurata.com Sales : C 00218912125435

www.amp.ly

- Y amppaints ──
- i amppaints
- amppaints

f amppaints1



دهانات المدينه مصرانه

Almadina Misurata Paints



Epoxy Anti Rust Znp

Epoxy paint is a high-end structural finish resistant to corrosion and corrosion of iron and steel A two-component solvent-based solvent based on epoxy resins and a special amino acid And granules of zinc phosphate

Application

Description

and features

1 -Paint tanks, pipes, fittings and metal structures exposed to the influence of chemical agents.

2 -Painting of roads, bridges and water and sewage plants.

- 3 Treatment and protection of reinforcing steel for concrete.
- 4- Painting of towers of high pressure and iron Hanger zinc.

Physical constant Operating period 1.52 kg / l Operating period 3 hours Full consolidation period 2 hours Consumption rate 5 m² / kg Weight 4 Kilo Mixing ratio 1.25 B : 8.1A Thinner Acrylic Thinner Tools Image: Second Sec	nediately	Health & 23 Safety	
Operating period 1.52 kg / 1 Drying time 3 hours Full consolidation period 2 hours Consumption rate 5 m² / kg Weight 4 Kilo Mixing ratio 1.25 B : 8.1A Thinner Acrylic Thinner Image: Second		n	
Operating period 1.52 kg / 1 Drying time 3 hours Full consolidation period 2 hours Consumption rate 5 m² / kg Weight 4 Kilo Mixing ratio 1.25B : 8.1A Thinner Acrylic Thinner			
Physical constant Operating period 1.52 kg / l Operating period 3 hours Drying time 3 hours Full consolidation period 2 hours Consumption rate 5 m² / kg Weight 4 Kilo Mixing ratio 1.25B : 8.1A		Tools	
Operating period 1.52 kg / 1		C V M	
Color white and other color Percentage of solids 75% Density (kg / l) 46% -62%		Physical Constant	

Marketing : C 00218918000047 Marketing@almadinamisurata.com Sales : **C** 00218912125435

- ly
- amppaints

f amppaints1

amppaints

amppaints