



دهانات المدينة مسرة

Almadina Misurata Paints | AMP



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Plastico 2021

Emulsion paint for interior use matte high quality white braying excellent covering power composed of acrylic emulsion easy to use with a smooth and soft surface high covering power manufacture from high-quality raw products use for concrete surfaces cement and gypsum.

- 1- The surfaces must be flat; cleaned and completely dry.
- 2- Apply a layer for new surfaces in (Alzawaq insulator).
- 3- Apply two or three layers (Almedina misurta putty) horizontally and longitudinally then do the surface sanding and clean the dust.
- 4- Apply a coat of paint (plastico) after dilution between 10% - 15% water depending on the surface and the thickness of the layer.

| | |
|------------------|-------------------------------------------------------|
| Color | White |
| Relative density | 1.60 – 1.58 ± 0.05 kg / liter |
| Viscosity | 115 : 120 |
| Power covering | 6 – 8 m ² per kg |
| PH | 9 ± 0.5 |
| Drying | touch drying at 30 min and complete drying at 6 hours |
| Flammability | not |
| Dilution | with water |
| Weight | 10 kg - 18 kg |



Brush



Roller



Spray gun

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 - This product is free of polluted materials to the environment.