

Description and

features

Physical

constant

Apply

Storge

دهانانت المدينه مصرانه

Almadina Misurata Paints



ISOCOLL C 2

Conforms to European standards En12004/C2

Isocoll is a quick-setting and quick hydration powder adhesive based on Portland cements, aluminous cements and fillers of selected grain size (white quartzes), ideal for laying marble, granite and natural stones. FIELDS OF APPLICATION Laying floors and walls of marble, granite and natural stones both indoor and outdoor. Overlaying of ceramic on ceramic and stone on stone after application of primer IMPORTANT -Do not use at temperature below 5°C (41°F) or higher than 35°C (95°F) -Do not use on wood substrates -Do not use on not matured concrete -Do not use for laying plasterboards -Do not use for laying tiles requiring adhesive thickness over 20 mm. powder APPEARANCE white - grey Color FLAMMABILITY no no TOXICITY 12 months in original packing and in dry environment STABILITY abt. 6 - 6.5 litres of water each 25 kg of powder MIXING RATIO 1.6 kg/L MIXTURE DENSITY 12.8 MIXTURE PH 1-2 hours MIXTURE SHELF-LIFE between 5°C and 35°C (41°F and 95°F) APPLICATION TEMPERATURE at 20°C (68°F) and 60% R.H. 25 minutes OPEN TIME within 15 minutes after laying TILE ADJUSTMENT (on floor) 12 to 24 hours after laying PEDESTRIAN TRAFFIC 2 to 3 hours after laying tiles (depending on absorption) IOINT MAKING ON WALLS

6 to 8 hours after laying tiles

PREPARING THE MIXTURE

JOINT MAKING ON FLOORS

 Mix 25 kg of Isocoll with 6-6.5 litres of clean water, possibly using a low-speed mixer, until to obtain a homogeneous mixture without lumps. Let the mixture stand 5 minutes about then mix again, at least 30 seconds, before using. The prepared mixture, mixed again immediately before use/application, has a shelf-life of about 1-2 hours (according to environmental conditions: temperature, ventilation, etc.).

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.

3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .

f amppaints1

amppaints

4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak Marketing : 💽 00218918000047 🖂 marketing@almadinamisurata.com

Sales : **C** 00218912125435

www.amp.ly

- y amppaints
 - 🗿 amppaints