







## Al Zawaq Insulator

**Description** and features High quality interior and exterior Acrylic insulator paint , using for insulating the cement, concrete and gypsum surfaces ,Prevents water permeability , High flexibility , Able to fill gaps Extra adhesion , Humidity high resistance , Made from High quality materials that resistant all weather conditions .

**Application** 

- 1 The surfaces must be flat, clean and completely dry.
- 2 First , Apply one coat with ( Al zawaq Insulator ) thinning by 30% water.
- 3 Apply two coats with ( Al zawaq Insulator ) with lengthwise and widthwise .

**Physical** constant

Color White

Viscosity 115:120 krebs

spreading rate 10 - 12 m<sup>2</sup> Depending on the thickness of the paint layer

 $8 \pm 9$ 

Specific gravity  $1.16 \pm 0.05 \text{ Kg/l}$ 

Thinner water

Packaging 3.5 kg - 13 kg

**Tools** 



Brush



Roller



Spray gun

**Storage** 

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Sales:

00218912125435

amppaints1



amppaints

www.amp.ly



