



Kelmingaro

Description and features

Emulsion paint , economic, interior, with high viscosity, excellent hiding power and high smoothness, made of high quality acrylic material, available in white and used on interior surfaces "cement , concrete and gypsum".

Application

- 1- All surfaces should be flat, clean and completely dry to be painted
- 2- Apply the new surfaces with Primer Interior (Al zawaq insulator)
- 3- Apply two or three coats with wall Putty " Almadina Misurata " lengthwise, use sanding paper and then clean the dust.

Physical constant

Color	White
Specific gravity	1.65 : 1.7 kg / l
Viscosity	125 : 135 Krebs
Spreading rate	4 : 6 m ² / kilo
PH	8.5 ± 0.5
Dry to touch	1/2 hours and completely dry after 6 hours.
Flash Point	Non flammable
Thinner	Water
Thinning	water by 15% first coat ,10% second coat of total weight, depending on the thickness of the paint and the state of the surface to be coated.
Weight	18 kg

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

