



Roads & Pavements Paints

Description and features

acrylic paint, high-quality, Factory according to environmental standard specification 584 for 2009 for road marking paints resistance to weather conditions ,chemical and petroleum materials, anti-friction, , made from the finest raw material in the world, used for roads planning and Runways and parking lots , Sport stadiums and for painting sidewalks

Application

- 1 - Surface must be soft ,clean, free of dirt, oil and grease to be painted.
- 2 - The apply by spray machine prepared for that, after dilution according to the instructions.

Physical constant

Color	Black, white, yellow ,
Solids ratio	Not less than 75% by
Specific gravity	weight 1.55 kg / lt
Coverage	4 : 5m ² / kg
Minimum thickness of the layer	500 μ
Dry to touch	5 minutes
Completely drying time	15 minutes
Packing	16 kg
Diluent	lacquer thinner 20%

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight. Storage is done at a temperature of 25°± 2.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

