



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Health & Safety

Graphite

Acrylic textured paint with grains quartz ,high-quality, interior and exterior, resist to all weather conditions, water-repellent, extreme gluing to surfaces, anti-friction, constant colors , gives a beautiful decorative forms, used to paint buildings from abroad, for decoration and weather protection .

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Apply the new surfaces with “ AlZwaq Insulator Almadina Misurata”
- 3 - Apply coat of “Graphite Almadina Misurata” according to required shape and decoration

Color	Available in 23 colors by catalog
Specific gravity	1.85 ± 0.05 kg / l
Viscosity	300: 390 g / cm
Spreading rate	3.5 : 4 m ² /18 kg
PH	8 : 9
Drying time	dry to touch ½ hours and completely dry after 24 hours
Flash Point	Non – Flammable
Thinner	Water when needed
Packaging	18 kg



Trowels

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@aladinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints