



دهانات المدينة مسرارة

Almadina Misurata Paints | AMP®



Sealer nitro

Description and features

Nitro Cellulose Paint, transparent, high quality, quick drying, with a very high viscosity and high gluing power, works to fill wood pores, gives a silky smooth surface after sanding process, made from the finest raw material in the world, used for all the woodwork of doors, windows and Household Furniture.

Application

Apply Sealer Doco paint "Almadina Misurata" after thinning with hot tanner, to get the desired viscosity of paint, two hours after coating, using sanding paper with an appropriate way.

Physical constant

Color	Transparent slant yellowing
Viscosity	After thinning with 2 sealer : 1 Thinner it's given 85 krebs at 25°
Dry to touch	15 minutes
Complete drying	60 minutes
Thinner	(Almadina misurata lacquer thinner)
Consumption rate	9 : 10 m ² /kg
Packaging	3 kg

Tools



Brush



Spray gun

Storage

Product should be stored in the original package for 18 months from the production date, store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

Twitter icon amppaints

Instagram icon amppaints

www.amp.ly