



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Description and features

Acrylic textured paint, exterior, high quality, easy to use, water repellent, resistant to all weather conditions, resistant to erosion and spalling, helps to hide plaster defects, has coarse quartz grains that gives elegant decorative look, made from the finest materials in the world, and design and applied on building and facility near to the sea, available in white and all colors.

Application

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Apply the new surfaces with "ALZwaq Insulator".
- 3 - Apply two coats of Shield Coarse "Almadina Misurata".

Physical constant

Color	Available in 23 colors by catalog
Gloss	quarter - Gloss (light gloss)
Viscosity	25 g/cm ³ at 25 °
Specific gravity	1.46 ± 0.05 Kg/l
Spreading rate	2 m ² / Liter depend on coating thickness
Coat Drought	20 minutes
Completely Dry	24 hours
Thinner	Water
Washability	High Washability
PH	9 ± 8.5
Packaging:	10 lt



Roller

Tools

Storage

Product should be stored in the original package for 12 months from the production date, store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints