



دهانات المدينة مصراطة

Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Water Alkyd «semi gloss»

A New generation of paints (water base), it has the same specifications of Alkyd paints , composite from pure Acrylic , for interior and exterior surfaces, using for cement , concrete and gypsum surfaces, High quality, Silky smooth surfaces, Extra whiteness, Highly washable, Anti-Bacterial, High coverage

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat for the new surfaces by (Alzawaq insulator)
- 3 - Apply two or three coats of (putty Almadina misurata) with lengthwise and widthwise, sand it and clean the dust.
- 4 - Apply one preparation coat of (latex plus matt Almadina misurata).
- 5 - Apply two coats of (water Alkyd Almadina misurata) after dilution with 10% water according to surface state and thickness of coat .

Finish	semi gloss
Color	White
Specific gravity	0.05 ± 1.2 kg/l
Viscosity	105 : 110 Krebs
Solid by volume	32 ± 2
Spreading rate	8-10 m ² /kilo thickness of 50 microns
PH	8 : 9
Dry to touch	1/2 hours and completely dry after 6 hours.
Flash Point	Non flammable
Thinning	Water by 10%
Weight	3 kg - 7 kg



Brush



Roller



Spray gun

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints