



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Bitumen «Emulsion»

High-quality Bitumen (Emulsion) paint, resistant to all weather conditions ,made of the finest materials in the world, used to insulate roofs of buildings and isolate Bathrooms foundations, concrete surfaces exposed to harmful groundwater pressure and basements, And ground water tanks and the top of the outside and used to glue cork panels and foam insulating layer and used under the Initial premade bitumen rolls .

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Must Mixing well until get completely homogeneous liquid before use.
- 3 - Must paint Preparation surface of "Bitumen (Emulsion)"Almadina Misurata" thinning by 30%,with water depend on permeability of surface.
- 4 - Lengthwise coat should be painted after 2 hours from " Almadina Misurata Bitumen(Emulsion) Preparation surface.
- 5 - Sideways coat should be after 2 hours from first coat

Color	Black after drought
Specific gravity	1.05 ± 0.02 Kg/l
Viscosity	120 Krebs
Spreading rate	1m ² / kg/face
Thinner	water and for spray thinning by 20%
Packaging	15 kg



Mop



Brush



Roller



Spray gun

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.