



# دهانات المدينة مسرارة

Almadina Misurata Paints | AMP®



## Roof coatings

### Description and features

high quality water base paint insulator acrylic, exterior resistance to climate weather. using this paint to insulate roofs and concrete water tanks , water baths ,and hospitals against to humidity and water. resistance to bacteria and fungai.frindly to environmental. low voc

### Application

- 1-should be surfaces dry, clean and free of oils and greases
- 2- should be fill all of pores and gapes by using (mastic almadina) before application
- 3- you can dilute the product by 30% water to fill gapes
- 4- you can use roller, brush or mop , don't dilute product to apply finish coat
- 5- Coverage rate is 1 kilo to 1 m<sup>2</sup>

### Physical constant

Colour	white
Specific gravity	1.35 kg/ltr
Viscosity	35 - 40 grm/s
Coverage rate	1 kg to 1 m <sup>2</sup>
Dilutions	water
PH	9 - 8
Packing	3 kg , 13 kg

### Tools



Mop



Brush



Roller

### Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

### Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

Twitter icon amppaints

Instagram icon amppaints

[www.amp.ly](http://www.amp.ly)